

a front facing vent located in a forwardly facing portion of the frame to input

6 exterior air moving relatively towards the front lens,

a channel located in the frame between the front facing vent and the interior

8 space to direct the exterior air from the front facing vent to the interior
space,

10 dispersing [disbursing] means associated with the channel for dispersing the

exterior air across a greater area than the front facing vent including

12 towards an inside surface of the front lens and having a rear wall opposite

the front facing vent and located in the channel for deflecting the exterior

14 air towards the interior space and partly forwardly against an inside surface

of the front lens and an inlet porous foam located in the channel between

16 the front facing vent and the rear wall, and

an outlet vent located in the frame for allowing air from the interior space to

18 exit the goggle.

2. (amended) The goggle of claim 1 wherein

2 an outlet porous foam having a total porosity of a first characteristic covers
the outlet vent and

4 the [disbursing means includes an] inlet porous foam has [having] a total
porosity of a different characteristic than the outlet porous foam and is

6 located within the channel so that exterior air from the front facing vent
moves through the inlet porous foam.

Cancel claim 5 without prejudice.

Claim 6, line 1, delete "claim 5" and insert - claim 1 -.

Cancel claim 8 without prejudice.

Claim 9, line 1, delete "claim 8" and insert - claim 1 -.

Q3 § 10. (amended) A goggle comprising:

2 a front lens,

Q3 3 a frame having a top section, side sections and a bottom section for

4 supporting the front lens in spaced relation in front of a wearer's face to
5 define an interior space,

6 a front facing vent located in a forwardly facing portion of the frame to input
7 exterior air moving relatively towards the front lens, and having [The goggle
8 of claim 1 wherein the front facing vent has] an inlet opening of first area
9 in the frame and spaced therefrom an exit opening of second area in the
10 frame [which is contiguous with the channel, the inlet opening being of
11 greater area than a reduced area of the exit opening so as to increase the
12 velocity of the exterior air while moving through the front facing vent.]

13 a channel located in the frame between the front facing vent and the interior
14 space to direct the exterior air from the front facing vent and through the
15 exit opening to the interior space,

16 the frame includes surrounding walls from the inlet opening to the exit opening
17 in order to define the front facing vent, at least certain of the surrounding
18 walls being slanted with respect to frontal exterior air moving directly
19 towards the front lens so as to deflect sideways at least portions of the
20 frontal exterior air as it is directed into the channel, and

21 an outlet vent located in the frame for allowing air from the interior space to
22 exit the goggle.

[Claim 11, line 1, delete "reduced" and insert - second -; same claim, line 2,
delete "greater" and insert - first -

Q3 10 12. (amended) The goggle of claim 10 wherein the frame includes at least two

2 [surrounding walls from the] inlet openings [to the exit opening] in order to define
3 the front facing vent, at least certain of the surrounding walls of one of the inlet
4 openings being slanted in a first direction with respect to frontal exterior air

3
a 6 moving directly towards the front lens so as to deflect sideways in the first
direction at least portions of the frontal exterior air as it is directed into the
8 channel and at least other of the surrounding walls of the second of the inlet
openings being slanted in a second direction different from the first direction so
10 as to deflect sideways in the second direction at least portions of the frontal air
as it is directed into the channel, whereby the channel receives exterior air
directed in different directions into the channel.

Claim 13, line 1, delete "claim 1" and insert - claim 10 -.

Claim 15, line 1, delete "claim 1" and insert - claim 10 .

1618. (amended) A goggle comprising:

a 2 a front lens,
a frame having surrounding sections for supporting the front lens in spaced
4 relation in front of a wearer's face to define an interior space,
a plurality of front facing air scoops spaced across a forwardly facing
6 portion of the frame to input a large volume of exterior air moving
relatively towards the front lens with at least certain of the front facing
8 air scoops having an inlet opening in the forwardly facing portion of the
frame and spaced therefrom an exit opening in the frame, the inlet
10 opening having an area of substantially greater size than the exit opening
area to thereby increase the velocity of the exterior air as it moves
12 through said certain front facing air scoops,
dispersing means located in the frame between the plurality of front facing
14 air scoops and the interior space and contiguous with the exit opening for
substantially reducing the large volume of exterior air and dispersing the
16 exterior air into the interior space, and
an outlet vent located in the frame for allowing air from the interior space to
18 exit the goggle.